CSC-01/02, TSC-01/02/03 TBC-01, TCC-02







COFFEE CONTROLLER

Features:

- 16 X 2 LCD Display
- · Color(Red/Green) LED indicators for warmer & brew buttons
- 120VAC & 220VAC, 50/60HZ OPERATION
- HEAT SENSOR: THERMISTOR 80-100K OHMS AT 25 C
- 16 PIN MOLEX MODULAR LINK CONNECTOR
- REMOTE TRIAC: 40 AMPS, 400V HEATSINK REQUIRED
- Operating Temperature: 0-75° C (32-167° F)

Dimensions:

• 8.55" W x 3.60" H x 1.55" D

Warranty:

Every Renau product is thoroughly tested at numerous stages of production and comes with an extended three (3) year warranty.

Applications:

 Ideal for commercial foodservice decanter brewers with single, double, and triple warmers. Programmable software to adapt to different types of brewers

Benefits:

- Digital Control Module Provides precise control over all aspects of brewing: time, temperature, volume and specialty coffee needs, from pre-infusion to pulse-brewing to brew bypass/water only.
- Intuitive Scroll-Through Precision Programming
- Large bright clear display functions easily communicated. Adjust time, temperature, volume, brew settings and more.
- Small footprint requires minimal space
- Low power consumption
- Easily upgradeable and scalable to meet specific needs
- Fully-encapsulated for maximum environmental protection
- Tested for high level of reliability for commercial use
- Simple, inexpensive installation
- Recipe Customization Ready

Software:

- Access Features with Ease
- **Brew Recipes**
- Prime-Infusion
- Intermittent Brew Control
- Brew Using Time or Volume Control
- Warmer Temperature Control with Reservior Monitor
- Cold Brew Lock
- **Brew Count Odometer**
- Warmer Energy Save/ Auto-Off
- Access Lock Code








We do more than design. We invent.



Tel: 818.341.1994 ext. 349 info@renau.com www.renau.com



We do more than design. We invent.